

Rear Over Hang Limits

Robot Building Supplies is committed to providing a safe and healthy environment for employees, contractors and visitors. With this in mind you will be asked to adhere to the following guidelines to ensure your experience at our stores is both safe and hazard free.

Robot Building Supplies Pick up Guidelines.

Robot Building Supplies is committed to servicing our clients' needs in an efficient, professional and safe manner. A number of products come in long lengths. To facilitate this we offer an onsite cutting service (for various products), an offsite cutting service (for various products) and a delivery service with the specified lead times and fees.

However, if you wish to collect your product from one of our stores please be advised that in accordance with legislative requirements we will use the following guidelines to ensure your vehicle is suitable to carry the material.

Rear overhang limits. (See Vic Roads 'Rear Overhang Limits for Cars and Trucks in Victoria)

- To reduce rear overhang, loads on motor vehicles may protrude up to 1.2 metres from the front of the vehicle. A load may only project 150mm from the outermost part of either side of the vehicle. However the maximum overall width for any vehicle and any load is 2.5 metres.
- The maximum rear overhang is 60% of the wheelbase. This measurement is not taken from the rear of the vehicle but the centre of the rear axle.

Trailers: the addition of a trailer does not allow a greater rear overhang on the towing vehicle. The load must fit within the carrying area or body.

Pig Trailers: the rear overhang must not exceed the length of the load carrying area or the body ahead of the overhang line.

Dog Trailers: For dog trailers and semi-trailers the rear overhang must not exceed 60% of the distance from the point of articulation at the front of the trailer to the overhang line.

Exclusion zones

You are welcome to assist with the hand-loading of products onto and into your vehicle. However, as soon as any plant (forklift or crane) needs to become involved in the process you are to remain in our exclusion zone. The store person will direct you to this zone. You are to stay a minimum of three metres away from the operating plant at all times and within peripheral vision (eye sight) and audible reach of the forklift operator.

Robot Building Supplies reserve the right to refuse to serve any vehicle that falls outside of these guidelines.